

**IP SPEED DOME CAMERA**

**OD-EPI 723 PR**



- ❖ سنسور تصویر CMOS 2 Mega pixel effective pixel
- ❖ High speed Auto focus lens (4.8-173mm)
- ❖ حداقل روشنایی 0.05lux
- ❖ H.264 and MJPEG & H.265
- ❖ زوم اپتیکال 36X
- ❖ WDR( UP TO 80db)
- ❖ AWB
- ❖ دارای IR تا فاصله 150 متر (adaptive)
- ❖ با قابلیت Wiper
- ❖ کلاس عایقی IP66 HOUSING
- ❖ قابلیت پوشش ضد خوردگی (به صورت سفارشی)

## OD-EPI 723 PR

<b>CAMERA</b>	<b>Image Sensor</b>	1/2.8" CMOS 2 MP CMOS
	<b>Minimum Illumination</b>	0.05 Lux
	<b>Dynamic Range</b>	UP TO 80 db
	<b>S/N RATIO</b>	More than 48dB
	<b>Shutter Speed</b>	1/2 s to 1/10,000 s, 21 steps
	<b>Sync System</b>	Internal Synchronization
	<b>White Balance</b>	Auto, ATW, Indoor, Outdoor
	<b>Zoom Ratio</b>	Optical Zoom 36x ,
	<b>Focal Length</b>	4.8 ~ 173mm
	<b>PAN/TILT Angle</b>	360° endless rotation, 180° Auto rotate
	<b>Preset Position</b>	255
<b>Number of Effective Pixels (HxV)</b>	1920x1080 (HxV)	
<b>Camera Features</b>	<b>DAY/NIGHT</b>	YES and ICR
	<b>Noise Reduction</b>	Yes
	<b>Image Stabilizer</b>	Yes
	<b>Video Buffer</b>	24MB Max
<b>Image</b>	<b>Video Compression Format</b>	H.264,MJPEG , H.265
	<b>Codec Streaming Capability</b>	Dual Streaming
	<b>Maximum Frame Rate</b>	H.264 : Up to 30FPS (1920*1080) H.265 : Up to 30FPS (1920*1080)
<b>Audio</b>	<b>Audio Compression Format</b>	G.711 & G.726

**OD-EPI 723 PR**

<b>Network</b>	<b>Protocol</b>	IPv4 , IPv6 , TCP, UDP, HTTP, HTTPS, FTP, SNMP
	<b>ONVIF Conformance</b>	Yes
	<b>WEB BROWSER</b>	Internet Explorer 8 or above, Chrome, Firefox
<b>Interface</b>	<b>Network Port</b>	10Base-T/100Base-TX (RJ-45)
	<b>Sensor Input</b>	1 Input/ 1Output
	<b>Alarm Output</b>	1 , 24V AC/DC , 3A (mechanical relay outputs electrically isolated from the camera)
	<b>Microphone Input</b>	EX Connector
<b>General</b>	<b>Power Requirements</b>	AC 24V , 3 A
	<b>Security</b>	User Account and Password Protection
	<b>Fan and Heater</b>	Yes
	<b>operating Temperature</b>	-30 °C ~ 70 °C
	<b>Operating Humidity</b>	20% to 80%
	<b>Ingress Protection</b>	IP66