

IP BULLET CAMERA

OD-VPI 330 MLP



- ❖ سنسور تصویر **3** مگا پیکسل (2048*1536) CMOS SONY SENSOR
- ❖ لنز موتورایز 2.8-12 mm با قابلیت Auto focus
- ❖ قابلیت فشرده سازی با فرمت H.265 و M-JPEG, H.264
- ❖ قابلیت ارسال دو stream به صورت مجزا
- ❖ قابلیت پشتیبانی از کارت حافظه
- ❖ پشتیبانی از پروتکل های : IPV4 ، UDP ، TCP ، HTTP ، DHCP ، DDNS
- ❖ قابلیت دید در شب
- ❖ قابلیت پردازش هوشمند تصویر (سفراری)
- ❖ قابلیت POE
- ❖ گستره دینامیکی (True WDR up to 120dB)
- ❖ ضد ضربه
- ❖ قابلیت ارتباطی ONVIF
- ❖ کلاس حفاظتی IP66

OD-VPI 330 MLP

Camera	IMAGE sensor	Type: 1/2.8 inch Sony Progressive Scan CMOS Pixels: 2048*1536 (3MP)
	FPS	FPS by user (1-30)
	LENS	2.8-12 mm Vari-Focal,3 Mega Pixel
	Adjustment	Motorized zoom, Auto Focus
	Shutter	Fixed (1/25s to 1/10000s) /Auto
	Resolutions (H× V)	1920*1080
	White balance	Auto ,Manual , Selectable
	3D Noise reduction	Yes
	Dynamic Range	True WDR up to 110dB
	Bandwidth Management	Variable & certain Bit rate
	Privacy Mask	Four independent areas
	DAY/NIGHT	True D/N/ Auto(IRC), Manual
	Minimum Illumination (color)	0.1 Lux without IR
	Minimum Illumination (B/W)	0.05 Lux with IR LED
Video	VIDEO COMPRESSION	H.264B/H.264H/H.264M/MJPG/H.265
	STREAMING	Main stream: Multicast off 2048*1536@ 30FPS/ 1920*1080@30fps/1280*720@30FPS
		Sub stream : Multicast off 704*576@30fps/640*480@30fps/640*352@30fps/320*240@30fps
		3main Stream + 3 sub Stream: Multicast on
Watermark	Yes	
Audio	AUDIO	Linear Audio Input /Output Interface
	AUDIO IN	Yes (option)
	AUDIO Out	Yes (option)
	Standard	G.711A, G.726, G.711U
Network	SECURITY	Password protection, user access privilege ; Server platform
	Unit configuration	Via web browser or configuration manager
	Connectivity	ONVIF
	Ethernet	10/100 Base-T, Auto negotiating
	Ethernet connector	RJ45 10M/100M Self, Auto negotiating
	Protocol	IPV4,UDP,TCP,HTTP,DHCP,DDNS,DNS,UPNP,PPOE,RTSP,FTP, NTP,IGMP,ICMP

OD-VEIP 330 MLP

System Integration	Alarm Input	Yes
	Alarm Out	Yes
Smart	Smart Detect Focus	Yes
	Motion Alarm	Yes
	Smart Cover Detect	Yes
	Motion Record	Yes
	Intelligent video analytic	Line crossing , region invitation (option)
Maintenance	Software update	Web Browser , Remotely
Recording	Recording on	FTP Server , SD CARD , RTSP, local on pc
	Recording mode	continuous, trigger, motion
	Memory card slot	Micro SD cards support up to 64GB (up to 128 GB optional)
Case	Material	Aluminum
	Color	White
Connection (Interface)	Ethernet Port	Yes
	Analog BNC	Yes (option)
	Alarm in	Yes (option)
	Alarm Out	Yes(option)
	Power in	Yes
	Reset Bottom	Yes
General	Power consumption	12v-DC
	Power	7.5 W with IR 5.5 W with out IR
	POE	IEEE 802.3AF
	Sensitivity	3200 K , 35 %IRE
	IR	30m
	Water / dust protection	IP66 / water & dust resistance
	Operating temperature	-5 ° c to +60 ° c
	Storage temperature	-30 ° c to +70 ° c
Operating humidity	Up to 95%	