

IP DOME CAMERA

OD-ECO-VPI 1031 PV



❖ سنسور تصویر 2 مگا پیکسل (1920*1080) - CMOS SONY SENSOR

❖ لنز ثابت 2.8mm

❖ قابلیت فشرده سازی با فرمت H264

❖ قابلیت ارسال دو Stream

❖ قابلیت تشخیص حرکت

❖ قابلیت دید در شب IR=20m

❖ پشتیبانی از پروتکل های : IPV4 ، UDP ، TCP ، HTTP ، DHCP ، DDNS

❖ قابلیت POE

❖ قابلیت ارتباطی ONVIF

❖ IP66

❖ Vandal proof

OD-ECO-VPI 1031 PV

Camera	IMAGE sensor	Type: 1/2.8 inch Sony Progressive Scan CMOS Pixels: 1920*1080 (2MP)
	FPS	FPS Adjustable by user (1-30)
	focal lens distance	2.8mm, 2 Mega Pixel lens
	SHUTTER	Fixed (1/25s to 1/10000s) / Auto
	Resolutions (H× V)	1920*1080 (2MP)
	White balance	Auto
	3D Noise reduction	Yes
	Dynamic Range	Up to 80dB
	Bandwidth Management	variable & certain bit rate
	Privacy Masking support	Yes
	DAY/NIGHT	True D/N/ Auto(IRC) , Manual
	Minimum Illumination (color)	0.1 Lux without IR
	Minimum Illumination (B/W)	0 Lux with IR LED
	Video	VIDEO COMPRESSION
STREAMING		Main stream: Multicast off 1920*1080@30fps/1280*720@30FPS
		Sub stream : Multicast off 704*576@30fps/640*480@30fps/640*352@30fps/320*240@30fps
		3main Stream + 3 sub Stream: Multicast on
Watermark	Yes	
Audio	AUDIO	Linear Audio Input /Output Interface
	AUDIO IN	Yes (option)
	AUDIO Out	Yes (option)
	Standard	G.711A , G.726 , G.711U
Network	SECURITY	Password protection, user access privilege ; Server platform
	Unit configuration	Via web browser or configuration manager
	Connectivity	ONVIF
	Ethernet	10/100 Base-T, Auto negotiating
	Ethernet connector	RJ45 10M/100M , Auto negotiating
	Protocol	IPV4,UDP,TCP,HTTP,DHCP,DDNS,DNS,UPNP,PPOE,RTSP,FTP,NTP,IGMP,ICMP

OD-ECO-VPI 1031 PV

Smart	Smart Detect Focus	Yes (option)
	Motion Alarm	Yes (option)
	Smart Cover Detect	Yes (option)
	Motion Record	Yes (option)
Maintenance	Software update	Web Browser , Remotely
Recording	Recording on	FTP Server, local on PC, SD card (option)
	Recording mode	Continuous, trigger, by alarm (Motion and etc)
Case	Material	Aluminum
	Color	White
Connection (Interface)	Ethernet Port	Yes
	Power in	Yes
General	Power consumption	12v-DC
	Power	7.5 W with IR 5.5 W with out IR
	POE	IEEE 802.3AF
	Sensitivity	3200 K , 35 %IRE
	IR	20m
	Water / dust protection	IP66 / water & dust resistance
	Operating temperature	-10 ° c to +60 ° c
	Storage temperature	-20 ° c to +70 ° c
	Operating humidity	Up to 95%